



Fuente De Poder.
5Vdc- 10A.
Cod: 20110767018

TECHNICAL DATA		
OUTPUT	DC VOLTAGE	5V
	RATED CURRENT	10A
	CURRENT RANGE	0 ~ 10A
	RATED POWER	50W
	RIPPLE&NOISE (MAX)	80mVp-p
	VOLTAGE ADJ. RANGE	4.75~5.5V
	VOLTAGE TOLERANCE	±2.0%
	LINE REGULATION	±0.5%
	LOAD REGULATION	±1.0%
	SETUP,RISE TIME	500ms,30ms/230VAC 1200ms,30ms/115VAC at full load
HOLD UP TIME	600ms/230VAC 14ms/115VAC at full load	
INPUT	VOLTAGE RANGE	88 ~ 264VAC 125~373VDC (Withstand 300VAC surge for 5sec. Without damage)
	FREQUENCY RANGE	47~63 Hz
	EFFICIENCY	83%
	AC CURRENT	1.3A/115VAC 0.8A/230VAC
	INRUSH CURRENT	COLD START 33A/230VAC
LEAKAGE CURRENT	<2ma/240VAC	
PROTECTION	OVERLOAD	110~150% Rated output power (Protection Type: Hiccup mode,recovers automatically after fault condition is removed)
	OVER VOLTAGE	5.75~6.75V (Protection type : Hiccup mode,recovers automatically after fault condition is removed)

Dimensiones.

Terminal Pin No. Assignment

Pin No.	Assignment	Pin No.	Assignment
1	AC/L	4	DC OUTPUT -V
2	AC/N	5	DC OUTPUT +V
3	FG		

Diagrama.